



The purity of Sound

Dared HPA-55L Portable Headphone Amplifier



Specifications:

- Max. Power Output
2x300mW (Single-end output loading: 16 Ω)
2x1000mW (Balanced Output loading: 16 Ω)
- Frequency response: 10Hz-30kHz
- S/N Ratio: 98dB
- Max. Power Consumption: 3500mW
- Working hours of Batteries (Fully Charged); Over 12 Hours
- Input port: 3.5mm phono jack
- Headphone Output port: 3.5mm single-end phono jack output x1, 3.5mm Balanced phono jack output x1
- Input Impedance: 47k Ω
- Output Internal resistance: 5 Ω (Single-end), 10 Ω (Balanced)
- Damping Factor: 7
- Q Factor: 0.75
- Max. Signal input level: 3V (RMS)
- DV charging Power Supply: DC 12V 500ma
- Batteries rechargeable life time: over 500 times

WorldWide Sales & Marketing Office : Hong Kong
Luen Hing Electriccal (HK) Limited
聯興電業(香港)有限公司
Address: G/F., 152 Apliu Street, Shamshuipo, Kowloon, H.K
Tel: +852 2728 8745 Fax: +852 2729 2962
Email: worldsales@dared.com.hk

South East Asia Sales Office : Singapore
Address: 19 Burn Road, 01-01 Advance Building
Singapore 369974
Tel: +65 6828 1133 Fax: +65 6828 3313
Email: seasales@dared.com.hk

www.dared.com.hk